







CERIO

Preisliste gültig ab 19. Januar 2024

Info: ↓ = Preissenkung, ↑ = Preiserhöhung, ✓ = keine Veränderung

ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
UNMANAGED POE SWITCH SERIES			
CS-1005G-4PX	<p>5 Port 10/100/1000M Gigabit Switch with 4 Port PoE+ (60 Watt Power)</p> <p>The CERIO CS-1005G-4PX is a powerful and complying with IEEE 802.3af/at Power over Ethernet standard which provides DC 48-57V Gigabit over Ethernet cables high-performance Gigabit Ethernet switch, with all 5 ports capable of 10/100Mbps or 1000Mbps autonegotiation operation which means the switch could automatically negotiate with the connected partners on the network speed and duplex mode. It is ideal for micro-segmenting large networks into smaller, connected subnets for improved performance, enabling the bandwidth demanding multimedia and imaging applications. Moreover, the 10/100/1000Mbps autosensing ability provides an easy way to migrate 10Mbps to 1000Mbps network with no pain.</p>	148.00	✓
			
CS-1008G-8P (A3)	<p>8 Port 10/100/1000M Gigabit Switch with 8 Port PoE+ (140 Watt Power), 19"-Adapter incl.</p> <p>This switch supports 8 Port 10/100/1000M Gigabit port Power over Ethernet (PoE+), 10Mbps speed with 802.3at 30Watt PoE+ power output over distance up to 280 meters on RJ45 UTP cable. Up to 280m PoE distance allows you to expand your network via Ethernet cable to where there is no power line or outlet but where you want to fix devices such as APs, IP Cameras or IP Phones, etc.. No longer need to worry about the complicated cables and long distance which may cost you a lot of time and money. By integrating the data transmitting cable and power cord, it eliminates the effort constructing your network. Over current protection and circuit shorting protection are also supported to ensure the safety.</p>	235.00	✓
			
MANAGED POE SWITCH SERIES			
CS-2208G-8P (A2)	<p>Powerful high-performance 8 + 2 port Gigabit PoE+ Switch (140 Watt Power)</p> <p>Highlight Features: TX Auto-Negotiation • 8 Port Gigabit PSE / PoE function compliant with IEEE-802.3af class3/class2/class1 and IEEE802.3at class4 • Supports 2 Gigabit SFP uplinks ports for connecting MiniGBIC 1000Base SX/LX fiber modules (Option) • PoE Green Power Energy Saving function • Supports power of up to 30W/15.4W/7.5W/4W for each PSE/PoE port • internal 160 Watts power supply supports a maximum PoE power budget of 130 Watts • Supporting flow control (Half- & Full-duplex), store & Forward functionality • provides 9K Jumbo frames • LACP • IGMP • Supports Port Mirroring & file backup and recovery • Web-based management interface • tested for the use of DANTE™ audio networks</p>	340.00	✓
			
CS-2424G-24P	<p>Powerful high-performance 24 + 4 port Gigabit PoE+ Switch (360 Watt Power)</p> <p>Highlight Features: TX Auto-Negotiation • 24 Port Gigabit PSE / PoE function compliant with IEEE-802.3af class3/class2/class1 • Supports 4 Gigabit SFP uplinks ports for connecting MiniGBIC 1000Base SX/LX fiber modules (Option) • PoE Green Power Energy Saving function • Supports power of up to 30W/15.4W/7.5W/4W for each PSE/PoE port • internal 400 Watts power supply supports a maximum PoE power budget of 350 Watts • Supporting flow control (Half- & Full-duplex), store & Forward functionality • provides 9.6K Jumbo frames • LACP • IGMP/MLD • Supports RADIUS/TACACS+ and AAA Certified function • MAC/IPv4 and IPv6 ACL security management • DoS (Denial of Service) Defense for enhanced network security • Link Layer Discovery Protocol (LLDP) and LLDP-MED • Supports DHCP Snooping function to prevent access by unauthorized hosts and DHCP servers and supports DHCP Option 82 provides additional security • Supports Port Mirroring & file backup and recovery • Supports Event Log, Alarm Log, Security Log, Network Log, and Protocol Log • Supports GUI display for monitoring network data status by port, traffic analysis by port and device CPU and Memory loading for convenient administrative network analysis and management • Web-based management interface • tested for the use of DANTE™ audio networks</p>	1'190.00	✓
			
FIBER SFP MODULES for CS-2208G-8P & CS-2424G-4P			
SLC-SXM	1000BASE-SX/SC Multi-Mode Fiber SFP Module (550 meters)	80.00	✓
			
SLC-LXS	1000BASE-LX/SC Single-Mode Fiber SFP Module (10 Kilometers)	90.00	✓
			



Preisliste gültig ab 19. Januar 2024

Info: ↓ = Preissenkung, ↑ = Preiserhöhung, ✓ = keine Veränderung

ARTIKEL	BEZEICHNUNG	UVP (CHF)	Info
---------	-------------	-----------	------

HIGH END WAVE-2 ACCESS POINT • eXtreme Series

CS-CW400-A1



Greater performance, greater coverage, faster streaming

Highlight Features: 2.4GHz band supports standard 802.11bgn protocol • 5GHz band supports 802.11 an/ac wireless protocol • AC1300 wireless concurrent dual band WiFi • CAP mode with centralized management of up to 64 units of Aps • Chipset design provides enterprise grade CPU performance, allowing the device to handle up to 200 concurrent clients! • supports fast wireless roaming 802.11r protocol for seamless roaming and smart client handoff • AP Mode with Hotspot Portal Authentication, Pure AP Mode, and WISP / CPE Repeater Mode, Router AP Mode, CAP Mode • 2.4GHz with 400 Mbps / 5GHz with 867 Mbps • Built-in RADIUS authentication server & Captive Portal Authentication supports by remote RADIUS server, Local account, third-party OAuth2.0, LDAP (AD), POP3, Guest and remote bulk MAC adress..

280.00 ✓